



## Safety Data Sheet

Copyright,2022, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	28-1029-9	<b>Version number:</b>	4.00
<b>Issue Date:</b>	16/01/2022	<b>Supersedes date:</b>	10/04/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### IDENTIFICATION:

#### 1.1. Product identifier

3M™ EZ Sand Multi-Purpose Repair Material PNs 05887 35887, 55887

#### Product Identification Numbers

60-4550-5209-6      60-9801-0922-1

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Automotive., Used to reparaire plastic parts on vehicles

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

**Company Emergency Hotline:**EMERGENCY: 1800 097 146 (Australia only)

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:**

28-6974-1, 28-6979-0

One or more components of this KIT is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

### TRANSPORT INFORMATION

The Dangerous Goods Classification for the complete Kit is provided below.

**UN No.:** UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., ( Bisphenol A-Epichlorohydrin Polymer )

**Class/Division:** 9

**Packing Group:** III

**Marine Pollutant:** Bisphenol A Epichlorohydrin polymer

**Hazchem Code:** -3Z

**IERG:** 47

**Australian Dangerous Goods Code (ADG) - Road/Rail Transport**

**Special Instructions:** Not restricted, environmentally hazardous substance exception.

**International Air Transport Association (IATA)- Air Transport**

**Special Instructions:** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**Special Instructions:** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	28-6974-1	<b>Version number:</b>	3.00
<b>Issue Date:</b>	16/01/2022	<b>Supersedes date:</b>	10/04/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ EZ Sand Multi-Purpose Repair Material PNs 05887, 35887, 55887 - Accelerator (Part A)

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Part A side of 2-Part Epoxy Adhesive for Flexible Parts Repair

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.  
Serious Eye Damage/Irritation: Category 1.  
Skin Sensitizer: Category 1B.  
Carcinogenicity: Category 1A.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

**Signal word**

Danger

**Symbols**

Corrosion | Exclamation mark | Health Hazard |

**Pictograms**



**Hazard statements**

H315	Causes skin irritation.
H318	Causes serious eye damage.
H317	May cause an allergic skin reaction.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system.

**Precautionary statements**

**Prevention:**

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280F	Wear respiratory protection.

**Response:**

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

**Storage:**

P405	Store locked up.
------	------------------

**Disposal:**

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

May be harmful if swallowed.  
May be harmful if inhaled.  
Harmful to aquatic life with long lasting effects.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	40 - 70
Limestone	1317-65-3	10 - 30
Talc	14807-96-6	5 - 20
Oxide Glass Chemicals	65997-17-3	1 - 10
Tris(2,4,6-dimethylaminomonomethyl)phenol	90-72-2	1 - 5
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	0.1 - 1
Titanium dioxide	13463-67-7	< 1.0
Quartz	14808-60-7	< 0.5

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide.

**Condition**

During combustion.

Carbon dioxide.  
 Oxides of nitrogen.  
 Oxides of sulphur.  
 Toxic vapour, gas, particulate.

During combustion.  
 During combustion.  
 During combustion.  
 During combustion.

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Limestone	1317-65-3	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m <sup>3</sup>	
Titanium dioxide	13463-67-7	ACGIH	TWA:10 mg/m <sup>3</sup>	A4: Not class. as human carcin
Titanium dioxide	13463-67-7	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m <sup>3</sup>	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m <sup>3</sup>	A4: Not class. as human carcin

Talc	14807-96-6	Australia OELs	TWA(8 hours):2.5 mg/m3	
Quartz	14808-60-7	ACGIH	TWA(respirable fraction):0.025 mg/m3	A2: Suspected human carcin.
Quartz	14808-60-7	Australia OELs	TWA(8 hours):0.1 mg/m3;Limit value not established:	
Oxide Glass Chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CELL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

#### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following

respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Off-White
<b>Odour</b>	Strong Mercaptan
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>Not applicable.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	<i>Not applicable.</i>
<b>Flash point</b>	245.6 °C
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not classified
<b>Flammable Limits(LEL)</b>	<i>Not applicable.</i>
<b>Flammable Limits(UEL)</b>	<i>Not applicable.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	1.1 - 1.1 kg/l
<b>Relative density</b>	1.078 - 1.09 [Ref Std: WATER=1]
<b>Water solubility</b>	<i>No data available.</i>
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity/Kinematic Viscosity</b>	100 - 150 Saybolt Universal Second [Details:Pressflow Viscosity]
<b>Volatile organic compounds (VOC)</b>	1 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Volatile organic compounds (VOC)</b>	0.1 % weight [Test Method:calculated per CARB title 2]
<b>Percent volatile</b>	0.1 % weight
<b>VOC less H2O &amp; exempt solvents</b>	1 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Molecular weight</b>	<i>No data available.</i>

#### Nanoparticles

This material contains nanoparticles.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material is considered to be non reactive under normal use conditions

### 10.2 Chemical stability

Stable.

### 10.3. Conditions to avoid



None known.

#### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

#### 10.5 Incompatible materials

None known.

#### 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1 Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

#### Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

#### Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

#### Additional Health Effects:

#### Prolonged or repeated exposure may cause target organ effects:

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >5 - ≤12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >2,000 - ≤5,000 mg/kg
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Dermal	Rabbit	LD50 > 10,200 mg/kg
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Ingestion	Rat	LD50 2,600 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
Oxide Glass Chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide Glass Chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Tris(2,4,6-dimethylaminomonomethyl)phenol	Dermal	Rat	LD50 1,280 mg/kg
Tris(2,4,6-dimethylaminomonomethyl)phenol	Ingestion	Rat	LD50 1,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Limestone	Rabbit	No significant irritation
Oxide Glass Chemicals	Professional judgement	No significant irritation
Tris(2,4,6-dimethylaminomonomethyl)phenol	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

Quartz	Professional judgement	No significant irritation
--------	------------------------	---------------------------

### Serious Eye Damage/Irritation

Name	Species	Value
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Rabbit	Mild irritant
Talc	Rabbit	No significant irritation
Limestone	Rabbit	No significant irritation
Oxide Glass Chemicals	Professional judgement	No significant irritation
Tris(2,4,6-dimethylaminomonomethyl)phenol	Rabbit	Corrosive
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation

### Skin Sensitisation

Name	Species	Value
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Mouse	Sensitising
Tris(2,4,6-dimethylaminomonomethyl)phenol	Guinea pig	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified
Titanium dioxide	Human and animal	Not classified

### Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	In Vitro	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Oxide Glass Chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Tris(2,4,6-dimethylaminomonomethyl)phenol	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
------	-------	---------	-------

Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Oxide Glass Chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Quartz	Inhalation	Human and animal	Carcinogenic.

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Tris(2,4,6-dimethylaminomonomethyl)phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 75 mg/kg/day	90 days

(4:1), 2-hydroxy-3-mercapto-propyl ether						
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercapto-propyl ether	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 250 mg/kg/day	90 days
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercapto-propyl ether	Ingestion	endocrine system   heart   skin   immune system   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	90 days
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Oxide Glass Chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Tris(2,4,6-dimethylaminomonomethyl)phenol	Dermal	skin   liver   nervous system   auditory system   hematopoietic system   eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years

Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity**

**Acute aquatic hazard:**

GHS Acute 3: Harmful to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 3: Harmful to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Activated sludge	Experimental	3 hours	EC50	>1,000 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-	72244-98-5	Green algae	Experimental	72 hours	EC50	>733 mg/l

bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether						
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Water flea	Experimental	48 hours	EC50	12 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Zebra Fish	Experimental	96 hours	LC50	87 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Green algae	Experimental	72 hours	NOEC	338 mg/l
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Water flea	Experimental	21 days	NOEC	3.5 mg/l

ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether						
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Talc	14807-96-6		Data not available or insufficient for classification			N/A
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Tris(2,4,6-dimethylamino monomethyl)phenol	90-72-2		Experimental	96 hours	LC50	718 mg/l
Tris(2,4,6-dimethylamino monomethyl)phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
Tris(2,4,6-dimethylamino monomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
Tris(2,4,6-dimethylamino monomethyl)phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tris(2,4,6-dimethylamino monomethyl)phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7		Data not available or insufficient for classification			N/A
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l



Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	NOEC	60 mg/l

**12.2. Persistence and degradability**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
alpha-Hydro-omega-hydroxy-poly[oxy(methyl-1,2-ethanediyl)], ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	Experimental Biodegradation	28 days	CO2 evolution	5 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Limestone	1317-65-3	Data not available-insufficient			N/A	
Talc	14807-96-6	Data not available-insufficient			N/A	
Oxide Glass Chemicals	65997-17-3	Data not available-insufficient			N/A	
Tris(2,4,6-dimethylamino monomethyl)phenol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % BOD/ThBOD	OECD 301D - Closed bottle test
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available-insufficient			N/A	
Titanium dioxide	13463-67-7	Data not available-insufficient			N/A	
Quartz	14808-60-7	Data not available-insufficient			N/A	

**12.3 : Bioaccumulative potential**

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
----------	------------	-----------	----------	------------	-------------	----------

alpha-Hydro- omega- hydroxy- poly[oxy(meth yl-1,2- ethanediyl)], ether with 2,2- bis(hydroxymet hyl)-1,3- propanediol (4:1), 2- hydroxy-3- mercaptopropyl ether	72244-98-5	Estimated Bioconcentrati on		Log Kow	>1.2	Estimated: Octanol- water partition coefficient
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oxide Glass Chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tris(2,4,6- dimethylamino monomethyl)p henol	90-72-2	Experimental Bioconcentrati on		Log Kow	-0.66	830.7550 Part.Coeff Shake Flask
Siloxanes and Silicones, di- Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF-Carp	42 days	Bioaccumulatio n factor	9.6	Non-standard method
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

## SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes.

## SECTION 14: Transport Information

### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable

IERG: Not applicable.

### International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable.

Proper shipping name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## SECTION 16: Other information

#### Revision information:

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**



## Safety Data Sheet

Copyright, 2022, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	28-6979-0	<b>Version number:</b>	3.00
<b>Issue Date:</b>	16/01/2022	<b>Supersedes date:</b>	08/04/2019

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ EZ Sand Multi-Purpose Repair Material PNs 05887, 35887, 55887 - Part B (Base)

#### 1.2. Recommended use and restrictions on use

##### Recommended use

3M™ EZ Sand Multi-Purpose Repair Material PNs 05887, 35887, 55887 - Part B (Base)

For Industrial or Professional use only.

#### 1.3. Supplier's details

**Address:** 3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113  
**Telephone:** 136 136  
**E Mail:** productinfo.au@mmm.com  
**Website:** www.3m.com.au

#### 1.4. Emergency telephone number

EMERGENCY: 1800 097 146 (Australia only)

### SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

#### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2.  
Serious Eye Damage/Irritation: Category 2.  
Skin Sensitizer: Category 1.  
Carcinogenicity: Category 1A.  
Specific Target Organ Toxicity (repeated exposure): Category 1.

#### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

**Signal word**

Danger

**Symbols**

Exclamation mark |Health Hazard |

**Pictograms**



**Hazard statements**

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H350 May cause cancer.
  
- H372 Causes damage to organs through prolonged or repeated exposure: respiratory system.

**Precautionary statements**

**Prevention:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P280F Wear respiratory protection.

**Response:**

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  
- P308 + P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a POISON CENTRE or doctor/physician if you feel unwell.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337 + P313 IF eye irritation persists: Get medical advice/attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.

**Storage:**

- P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.

**Disposal:**

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other assigned/identified product hazards**

None known.

**2.4. Other hazards which do not result in classification**

May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Limestone	1317-65-3	10 - 30
Talc	14807-96-6	10 - 30
12-(Oxiranylmethoxy)-9-octadecenoic acid, 1,2,3-propanetriyl ester	74398-71-3	5 - 15
Glass, oxide, chemicals	65997-17-3	1 - 10
Siloxanes and Silicones, di-Me, reaction products with silica	Mixture	< 3
Stearic Acid	57-11-4	< 1.5
Quartz	14808-60-7	< 0.5

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Aldehydes.

Carbon monoxide.

**Condition**

During combustion.

During combustion.

Carbon dioxide.  
Hydrogen Chloride

During combustion.  
During combustion.

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**Hazchem Code:** •3Z

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Use personal protective equipment (eg. gloves, respirators...) as required.

**7.2. Conditions for safe storage including any incompatibilities**

Keep container tightly closed. Store away from heat. Store away from acids.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
CAS NO SEQ117921	1317-65-3	ACGIH	TWA(inhalable particulates):10 mg/m3	
CAS NO SEQ117922	1317-65-3	ACGIH	TWA(respirable particles):3 mg/m3	
Limestone	1317-65-3	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m3	A4: Not class. as human carcin
Talc	14807-96-6	Australia OELs	TWA(8 hours):2.5 mg/m3	
Quartz	14808-60-7	ACGIH	TWA(respirable	A2: Suspected human

			fraction):0.025 mg/m3	carcin.
Quartz	14808-60-7	Australia OELs	TWA(8 hours):0.1 mg/m3;Limit value not established:	
Stearates	57-11-4	ACGIH	TWA(respirable fraction):3 mg/m3;TWA(inhalable fraction):10 mg/m3	A4: Not class. as human carcin
Stearates	57-11-4	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
CERAMIC FIBERS	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
CERAMIC FIBERS	65997-17-3	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml	
CONTINUOUS FILAMENT GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A4: Not class. as human carcin
CONTINUOUS FILAMENT GLASS FIBERS, INHALABLE FRACTION	65997-17-3	ACGIH	TWA(inhalable fraction):5 mg/m3	A4: Not class. as human carcin
Glass filaments	65997-17-3	Australia OELs	TWA(as fiber)(8 hours):0.5 fibers/ml;TWA(8 hours):0.5 fibers/ml	
GLASS WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.
Glass, oxide, chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3	
ROCK WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.
SLAG WOOL FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.
SPECIAL PURPOSE GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

## 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:



Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

if this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Select and use gloves according to AS/NZ 2161.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Solid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Black
<b>Odour</b>	Little Odour
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	<i>Not applicable.</i>
<b>Melting point/Freezing point</b>	<i>No data available.</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	<i>Not applicable.</i>
<b>Flash point</b>	248.3 °C [ <i>Test Method:Estimated</i> ]
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Flammability (solid, gas)</b>	Not classified
<b>Flammable Limits(LEL)</b>	<i>Not applicable.</i>
<b>Flammable Limits(UEL)</b>	<i>Not applicable.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Vapor Density and/or Relative Vapor Density</b>	<i>No data available.</i>
<b>Density</b>	1 - 1.5 g/ml
<b>Relative density</b>	1 - 1.5 [ <i>Ref Std: WATER=1</i> ]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>

<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity/Kinematic Viscosity</b>	40 - 110 Saybolt Universal Second [ <i>Details: Pressflow Viscosity</i> ]
<b>Volatile organic compounds (VOC)</b>	1 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
<b>Volatile organic compounds (VOC)</b>	0.1 % weight [ <i>Test Method: calculated per CARB title 2</i> ]
<b>Percent volatile</b>	0.1 % weight
<b>VOC less H2O &amp; exempt solvents</b>	1 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]
<b>Molecular weight</b>	<i>No data available.</i>

**Nanoparticles**

This material contains nanoparticles.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3. Conditions to avoid**

Heat.

**10.4. Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.5 Incompatible materials**

Strong acids.

**10.6 Hazardous decomposition products****Substance**

Phosgene

Toxic vapour, gas, particulate.

**Condition**

Not specified.

Not specified.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction

(non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Moderate eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**

Pneumoconiosis: Sign/symptoms may include persistent cough, breathlessness, chest pain, increased amounts of sputum, and changes in lung function tests.

**Carcinogenicity:**

Contains a chemical or chemicals which can cause cancer.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg
12-(Oxiranylmethoxy)-9-octadecenoic acid, 1,2,3-propanetriyl ester	Dermal	Rabbit	LD50 > 2,000 mg/kg
12-(Oxiranylmethoxy)-9-octadecenoic acid, 1,2,3-propanetriyl ester	Ingestion	Rat	LD50 > 5,000 mg/kg
Glass, oxide, chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Glass, oxide, chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Stearic Acid	Dermal	Rabbit	LD50 > 2,000 mg/kg
Stearic Acid	Ingestion	Rat	LD50 > 5,000 mg/kg
Quartz	Dermal		LD50 estimated to be > 5,000 mg/kg
Quartz	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Talc	Rabbit	No significant irritation

Limestone	Rabbit	No significant irritation
Glass, oxide, chemicals	Professional judgement	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Stearic Acid	Rabbit	No significant irritation
Quartz	Professional judgement	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Talc	Rabbit	No significant irritation
Limestone	Rabbit	No significant irritation
Glass, oxide, chemicals	Professional judgement	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
Stearic Acid	Rabbit	No significant irritation

### Skin Sensitisation

Name	Species	Value
Siloxanes and Silicones, di-Me, reaction products with silica	Human and animal	Not classified

### Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Glass, oxide, chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
Stearic Acid	In Vitro	Not mutagenic
Quartz	In Vitro	Some positive data exist, but the data are not sufficient for classification
Quartz	In vivo	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
Talc	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
Glass, oxide, chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Stearic Acid	Ingestion	Rat	Not carcinogenic
Quartz	Inhalation	Human and animal	Carcinogenic.

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	prematuring & during gestation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Stearic Acid	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis   respiratory system	Not classified	Rat	NOAEL 18 mg/m3	113 weeks
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Glass, oxide, chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Stearic Acid	Ingestion	blood	Not classified	Rat	NOAEL Not available	6 weeks
Quartz	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

**Interactive Effects**

Not determined.

**SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

**12.1. Toxicity****Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

**Chronic aquatic hazard:**

GHS Chronic 2: Toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
Talc	14807-96-6		Data not available or insufficient for classification			N/A
12-(Oxiranylmethoxy)-9-octadecenoic acid, 1,2,3-propanetriyl ester	74398-71-3		Data not available or insufficient for classification			N/A
Glass, oxide, chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Glass, oxide, chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Glass, oxide, chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Glass, oxide, chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Mixture		Data not available or insufficient for classification			N/A
Stearic Acid	57-11-4	Green algae	Estimated	72 hours	EC50	>100 mg/l

Stearic Acid	57-11-4	Water flea	Estimated	48 hours	EC50	>100 mg/l
Stearic Acid	57-11-4	Bacteria	Experimental	18 hours	EC10	883 mg/l
Stearic Acid	57-11-4	Green algae	Estimated	72 hours	NOEC	100 mg/l
Stearic Acid	57-11-4	Water flea	Estimated	21 days	NOEC	100 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	EC50	440 mg/l
Quartz	14808-60-7	Water flea	Estimated	48 hours	EC50	7,600 mg/l
Quartz	14808-60-7	Zebra Fish	Estimated	96 hours	LC50	5,000 mg/l
Quartz	14808-60-7	Green Algae	Estimated	72 hours	NOEC	60 mg/l

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available-insufficient			N/A	
Talc	14807-96-6	Data not available-insufficient			N/A	
12-(Oxiranylmethoxy)-9-octadecenoic acid, 1,2,3-propanetriyl ester	74398-71-3	Data not available-insufficient			n/a	
Glass, oxide, chemicals	65997-17-3	Data not available-insufficient			N/A	
Siloxanes and Silicones, di-Me, reaction products with silica	Mixture	Data not available-insufficient			N/A	
Stearic Acid	57-11-4	Experimental Biodegradation	28 days	CO2 evolution	89 % weight	OECD 301B - Modified sturm or CO2
Quartz	14808-60-7	Data not available-insufficient			N/A	

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
12-(Oxiranylmethoxy)-9-octadecenoic	74398-71-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

acid, 1,2,3-propanetriyl ester						
Glass, oxide, chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	Mixture	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Stearic Acid	57-11-4	Estimated BCF - Other	28 days	Bioaccumulation factor	255	OECD 305E - Bioaccumulation flow-through fish test
Quartz	14808-60-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

#### 12.4. Mobility in soil

Please contact manufacturer for more details

#### 12.5 Other adverse effects

No information available.

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

### SECTION 14: Transport Information

#### Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Bisphenol A-Epichlorohydrin Polymer )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Not restricted, environmentally hazardous substance exception.

**Hazchem Code:** •3Z

**IERG:** 47

#### International Air Transport Association (IATA) - Air Transport

UN No.: UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Bisphenol A-



Epichlorohydrin Polymer )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Special Instructions:** Not restricted, as per Special Provision A197, environmentally hazardous substance exception.

**International Maritime Dangerous Goods Code (IMDG)- Marine Transport**

**UN No.:** UN3082

**Proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. , ( Bisphenol A-Epichlorohydrin Polymer )

**Class/Division:** 9

**Sub Risk:** Not applicable.

**Packing Group:** III

**Marine Pollutant:** Bisphenol A-Epichlorohydrin Polymer

**Special Instructions:** Not restricted, as per IMDG code 2.10.2.7, marine pollutant exception.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Australian Inventory Status:**

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

## SECTION 16: Other information

**Revision information:**

Complete document review.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

**3M Australia SDSs are available at [www.3m.com.au](http://www.3m.com.au)**