

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** **BODY 691 2:1 ULTRA HS CLEAR COAT SR****Article number:** 471**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

**Product category** PC9a Coatings and paints, thinners, paint removers**Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities**Environmental release category** ERC2 Formulation into mixture**Article category** AC1 Vehicles**Technical function** Dye**Application of the substance / the mixture** Surface protection**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

**Further information obtainable from:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

**1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

Fax: +44 28 90 24 80 30

Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Trade name: **BODY 691 2:1 ULTRA HS CLEAR COAT SR**

\* SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3      H226 Flammable liquid and vapour.



Skin Irrit. 2      H315 Causes skin irritation.

STOT SE 3      H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02      GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

n-butyl acetate

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241      Use explosion-proof [electrical/ventilating/lighting] equipment.

P261      Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405      Store locked up.

P501      Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:**

EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction.



· 2.3 Other hazards

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR****SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures****Description:** Mixture of hazardous substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 123-86-4	n-butyl acetate	30-<35%
EINECS: 204-658-1	 Flam. Liq. 3, H226	
Index number: 607-025-00-1	 STOT SE 3, H336	
RTECS: AF 7350000		
Reg.nr.: 01-2119485493-29-007		
01-2119485493-29-004		
01-2119485493-29-003		
01-2119485493-29-005		
01-2119485493-29		
CAS: 1330-20-7	xylene	15-<20%
EINECS: 215-535-7	 Flam. Liq. 3, H226	
Index number: 601-022-00-9	 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
RTECS: ZE 2100000		
Reg.nr.: 01-2119488216-32-001		
01-2119488216-32-002		
01-2119488216-32-003		
CAS: 112-07-2	2-butoxyethyl acetate	<2.5%
EINECS: 203-933-3	 Acute Tox. 4, H312; Acute Tox. 4, H332	
Index number: 607-038-00-2		
RTECS: KJ 8925000		
Reg.nr.: 01-2119475112-47-0002		
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≥0.25-<1%
EINECS: 255-437-1	 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
	 Skin Sens. 1, H317	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:** In case of unconsciousness place patient stably in side position for transportation.**After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

In case of skin contact DO NOT clean effected area with solvents or thinners. Take off all contaminated clothing at once. Wash skin thoroughly with neutral pH soap and water. In any suspicion that skin irritation persists call a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If symptoms persist consult doctor.**4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Continue on page 4

GB

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR**

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**  
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- **5.6 Fire and explosion Hazards**
- **Speial protective equipment and fire fighting procedures:**  
Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

\* **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

\* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

\* **SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
  - **Ingredients with limit values that require monitoring at the workplace:**
- 
- 123-86-4 n-butyl acetate  
WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

Continue on page 5

GB

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR****1330-20-7 xylene**WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppmLong-term value: 220 mg/m<sup>3</sup>, 50 ppm

Sk; BMGV

**112-07-2 2-butoxyethyl acetate**WEL Short-term value: 332 mg/m<sup>3</sup>, 50 ppmLong-term value: 133 mg/m<sup>3</sup>, 20 ppm

Sk

· **Regulatory information** WEL: EH40/2020**Ingredients with biological limit values:****1330-20-7 xylene**

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**

The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the baseis of the different substances in the preparation.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

Continue on page 6

GB

Trade name: **BODY 691 2:1 ULTRA HS CLEAR COAT SR**

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

\* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

· **Form:** Liquid

· **Colour:** Transparent

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Mixture is non-soluble (in water).

· **Change in condition**

· **Melting point/freezing point:** Undetermined.

· **Initial boiling point and boiling range:** 124-128 °C (123-86-4 n-butyl acetate)

· **Flash point:** 23 - 60 °C

· **Flammability (solid, gas):** Not applicable.

· **Autoignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

· **Explosion limits:**

· **Lower:** 1.1 Vol %

· **Upper:** 7.5 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa

· **Density at 20 °C:** 0.88104 g/cm<sup>3</sup>

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **water:** Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity:**

· **Dynamic:** Not determined.

· **Kinematic:** Not determined.

· **Solvent content:**

· **Organic solvents:** 47.7 %

· **VOC (EC)** 420.6 g/l

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR****Solids content (volume):** 52.2 %**9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity**

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**

**ATE (Acute Toxicity Estimates)**

Dermal LD50 11,490 mg/kg (rabbit)

Inhalative LC50/4 h 65.1 mg/l

**123-86-4 n-butyl acetate**

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 &gt;5,000 mg/kg (rabbit)

Inhalative LC50/4 h &gt;21 mg/l (rat)

**1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

**112-07-2 2-butoxyethyl acetate**

Oral LD50 2,400 mg/kg (rat)

Dermal LD50 1,580 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

- **Primary irritant effect:**

- **Skin corrosion/irritation**

Causes skin irritation.

- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**

- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

- **Carcinogenicity** Based on available data, the classification criteria are not met.

- **Reproductive toxicity** Based on available data, the classification criteria are not met.

- **STOT-single exposure**

May cause drowsiness or dizziness.

- **STOT-repeated exposure** Based on available data, the classification criteria are not met.

Continue on page 8

GB

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR**

- **Aspiration hazard** Based on available data, the classification criteria are not met.

\* **SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **Additional ecological information:**· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.  
Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).· **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).· **12.6 Other adverse effects** No further relevant information available.\* **SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.· **Uncleaned packaging:**· **Recommendation:** Disposal must be made according to official regulations.· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.\* **SECTION 14: Transport information**· **14.1 UN-Number**· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**· **ADR**

UN1263 PAINT

· **IMDG, IATA**

PAINT

Continue on page 9

GB



Trade name: **BODY 691 2:1 ULTRA HS CLEAR COAT SR**

· 14.3 Transport hazard class(es)

· **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3
- **IMDG, IATA**



- **Class** 3 Flammable liquids.
- **Label** 3
- 14.4 Packing group
- **ADR, IMDG, IATA** III
- 14.5 Environmental hazards:
- **Marine pollutant:** No
- 14.6 Special precautions for user Warning: Flammable liquids.
- **Hazard identification number (Kemler code):** 30
- **EMS Number:** F-E,S-E
- **Stowage Category** A
- 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· **Transport/Additional information:**

· **ADR**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- **Transport category** 3
- **Tunnel restriction code** D/E

· **IMDG**

- **Limited quantities (LQ)** 5L
- **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1263 PAINT, 3, III

\* SECTION 15: Regulatory information

·3Y

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR****Hazard pictograms****Signal word** Warning**Hazard-determining components of labelling:**

n-butyl acetate

**Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category** P5c FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.**SECTION 16: Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H226 Flammable liquid and vapour.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**Contact:**

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

Continue on page 11

GB

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR**

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**

GB

Continue on page 12

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR****Annex: Exposure scenario****· Short title of the exposure scenario****· Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

**· Product category** PC9a Coatings and paints, thinners, paint removers**· Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities**· Article category** AC1 Vehicles**· Environmental release category** ERC2 Formulation into mixture**· Technical function** Dye**· Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**· Conditions of use** According to directions for use.**· Duration and frequency** Frequency of use:**· Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**· Physical state** Fluid**· Concentration of the substance in the mixture** The substance is main component.**· Used amount per time or activity** Smaller than 100 g per application.**· Other operational conditions****· Other operational conditions affecting environmental exposure** Use only on hard ground.**· Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid long-term or repeated skin contact.

Avoid contact with eyes.

**· Other operational conditions affecting consumer exposure** No special measures required.**· Other operational conditions affecting consumer exposure during the use of the product** Not applicable.**· Risk management measures****· Worker protection****· Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**· Technical protective measures**

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

**· Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Avoid contact with the eyes.

**Trade name: BODY 691 2:1 ULTRA HS CLEAR COAT SR**

Tightly sealed goggles

**· Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**· Environmental protection measures****· Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

**· Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

**· Disposal measures** Ensure that waste is collected and contained.**· Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Waste type** Partially emptied and uncleaned packaging**· Exposure estimation****· Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

**· Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.