

KOMODO® CUT 5 Safety Gloves

Intended Use

To protect the user from mechanical (tear, abrasion, cut & puncture) during mechanical tasks, whilst maintaining comfort and dexterity.

Trade Name	Materials	Cut Rating	Cuff Finishing	
KOMODO [®] Cut 5	Double dipped sandy nitrile.	5	Double stitched	Part No.
			elastic cuff.	Small
Colour	UOM			Medium
Red with white threads on cuff, black palm and fingers.	1 pair			Large
				Extra Large
				XX Large

Dimensions	Size	Palm width	Length (mm)
Millimetres (Inches)	Small	78 ± 3mm (3.07" ± 0.1")	240 (minimum) (9")
	Medium	84 ± 3mm (3.30" ± 0.1")	240 (minimum) (9")
	Large	94 ± 3mm (3.70" ± 0.1")	240 (minimum) (9")
	Extra Large	105 ± 3mm (4.13" ± 0.1")	240 (minimum) (9")
	XX Large	113 ± 3mm (4.45" ± 0.1")	240 (minimum) (9")
Thickness	Palm	Finger	
Millimetres (Inches)	1.25mm (49.2mils)	1.45mm (57.1mils)	

Packaging Configuration & Labelling				
Packaging	120 pairs per case			

(12 pairs per inner bag)

Barcodes



GS1 format



Performance level

Abrasion

Puncture

Cut

Tear

4

5

4

4

EN388

4544

Designing and manufacturing the world's best disposable and reusable protective gloves