



KOMODO® Mechanic's Glove

Intended Use

To protect the user from mechanical risks (tear, abrasion, cut & puncture) and light chemical risks during mechanical tasks, whilst maintaining comfort and dexterity. Double dipped nitrile coating for oil resistance.

Trade Name KOMODO® Mechanic's	Materials Double dipped sandy nitrile, fine cotton back of hand.	Cut Rating 1	Cuff Finishing Double stitched elastic cuff.
Surface Finishing Sandy grip texture on nitrile coated palm.	Colour Black with white details.	UOM 1 pair	

Dimensions	Size	Palm width	Length (mm)
Millimetres (Inches)	Small	84 ± 3mm (3.30" ± 0.1")	240 (minimum) (9")
	Medium	94 ± 3mm (3.70" ± 0.1")	240 (minimum) (9")
	Large	105 ± 3mm (4.13" ± 0.1")	240 (minimum) (9")
	Extra Large	113 ± 3mm (4.45" ± 0.1")	240 (minimum) (9")
	XX Large	120 ± 3mm (4.72" ± 0.1")	240 (minimum) (9")

Thickness	Palm	Finger
Millimetres (Inches)	1.10mm (43.3mils)	1.10mm (43.3mils)

Packaging Configuration & Labelling

Packaging 120 pairs per case
(12 pairs per inner bag)

Barcodes GS1 format

Performance level

EN388  4121	Abrasion	4
	Cut	1
	Tear	2
	Puncture	1

Part No.

Small	620601
Medium	620602
Large	620603
Extra Large	620604
XX Large	620605

