



Auto Refinishing Products

Page 1/18

Printing date 24.04.2020

Revision: 24.04.2020

Version number 14

Safety data sheet
according to 1907/2006/EC, Article 31

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

· **1.1 Product identifier**

· **Trade name:** **BODY P307 4:1 FILLING PRIMER**

· **Article number:** 140

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9b Fillers, putties, plasters, modelling clay

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Environmental release category** ERC2 Formulation into mixture

· **Article category** AC1 Vehicles

· **Application of the substance / the mixture**

Priming

Surface protection

2K Anticorrosive HS sanding/ Wet-on-wet filling primer 4:1

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **Further information obtainable from:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI,GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **1.4 Emergency telephone number:**

Regional Medicines and Poisons Information Centre NI

Pharmacy Department, Royal Hospital Suite

Grosvenor Road Belfast

Telephone: +44 28 90 63 2032

(Contd. on page 2)

GB

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 1)

Fax: +44 28 90 24 80 30
Emergency telephone: 844 892 0111
E-mail address: nirdic.nirdic@belfasttrust.hscni.net

* **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Warning

Hazard-determining components of labelling:

toluene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 2)












· **vPvB:** Not applicable.

* **SECTION 3: Composition/information on ingredients**

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Mixture of hazardous substances

· **Dangerous components:**

CAS: 123-86-4	n-butyl acetate	10-<15%
EINECS: 204-658-1	 Flam. Liq. 3, H226	
Index number: 607-025-00-1	 STOT SE 3, H336	
RTECS: AF 7350000		
Reg.nr.: 01-2119485493-29-007		
01-2119485493-29-004		
01-2119485493-29-003		
01-2119485493-29-005		
01-2119485493-29		
CAS: 1330-20-7	xylene	10-<15%
EINECS: 215-535-7	 Flam. Liq. 3, H226	
Index number: 601-022-00-9	 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
RTECS: ZE 2100000		
Reg.nr.: 01-2119488216-32-001		
01-2119488216-32-002		
01-2119488216-32-003		
CAS: 108-88-3	toluene	5-<10%
EINECS: 203-625-9	 Flam. Liq. 2, H225	
Index number: 601-021-00-3	 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304	
RTECS: XS 5250000	 Skin Irrit. 2, H315	
Reg.nr.: 01-2119471310-51-0000		
01-2119471310-51-0003		
01-2119471310-51-0005		
01-2119471310-51-0002		
01-2119471310-51-0027		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	2.5-<5%
EINECS: 265-199-0	 Flam. Liq. 3, H226	
Index number: 649-356-00-4	 Asp. Tox. 1, H304	
Reg.nr.: 01-2119455851-35-0001	 Aquatic Chronic 2, H411	
	 Acute Tox. 4, H332; STOT SE 3, H335-H336	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

* **SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 3)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

* **SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- **Speial protective equipment and fire fighting procedures:**
Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

* **SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

GB
(Contd. on page 5)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm
Long-term value: 220 mg/m³, 50 ppm
Sk; BMGV

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

Regulatory information WEL: EH40/2020

Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

Respiratory protection: Not required.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.


Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 5)

- **For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:**
The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.
- **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Rubber gloves
- **Eye protection:**
 Tightly sealed goggles
- **Body protection:** Protective work clothing

* SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Appearance:**

· **Form:** Fluid
· **Colour:** According to product specification

· **Odour:** Characteristic
· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· **Melting point/freezing point:** Undetermined.
· **Initial boiling point and boiling range:** 110-111 °C

· **Flash point:** 23 - 60 °C

· **Flammability (solid, gas):** Not applicable.

· **Autoignition temperature:** 370 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

· **Explosion limits:**

· **Lower:** 1.1 Vol %
· **Upper:** 7.5 Vol %

· **Vapour pressure at 20 °C:** 10.7 hPa

· **Density at 20 °C:** 1.493 g/cm³

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

· **water:** Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.

(Contd. on page 7)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 6)

- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 35.4 %
 - VOC (EC)** 528.0 g/l
 - Solids content (volume):** 63.8 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - **Acute toxicity** Based on available data, the classification criteria are not met.
 - **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Dermal LD50 17.213 mg/kg
Inhalative LC50/4 h >39.6 mg/l

471-34-1 calcium carbonate

Oral LD50 6,450 mg/kg (rat)

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)
Dermal LD50 2,000 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)
Dermal LD50 >10,000 mg/kg (rabbit)
Inhalative LC50/4 h >6.82 mg/l (rat)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)
Dermal LD50 (static) 12,124 mg/kg (rabbit)
Inhalative LC50/4 h 5,320 mg/l (mouse)

(Contd. on page 8)

Trade name: BODY P307 4:1 FILLING PRIMER

(Contd. of page 7)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)
Dermal LD50 >3,400 mg/kg (rab)
Inhalative LC50/4 h >10.2 mg/l (rat)

· **Primary irritant effect:**

· **Skin corrosion/irritation**

Causes skin irritation.

· **Serious eye damage/irritation** Based on available data, the classification criteria are not met.

· **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

· **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

· **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

· **Carcinogenicity** Based on available data, the classification criteria are not met.

· **Reproductive toxicity**

Suspected of damaging the unborn child.

· **STOT-single exposure** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure** Based on available data, the classification criteria are not met.

· **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **12.2 Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 8)

· **European waste catalogue**

HP3 Flammable
HP10 Toxic for reproduction
HP14 Ecotoxic

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.
· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

* **SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR, IMDG, IATA**

UN1263

· **14.2 UN proper shipping name**

· **ADR**

UN1263 PAINT

· **IMDG, IATA**

PAINT

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

3 (F1) Flammable liquids.

· **Label**

3

· **IMDG, IATA**



· **Class**

3 Flammable liquids.

· **Label**

3

· **14.4 Packing group**

· **ADR, IMDG, IATA**

III

· **14.5 Environmental hazards:**

· **Marine pollutant:**

No

· **14.6 Special precautions for user**

Warning: Flammable liquids.

· **Hazard identification number (Kemler code):**

30

· **EMS Number:**

F-E,S-E

· **Stowage Category**

A

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 9)

· Transport category	3
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

* **SECTION 15: Regulatory information**

·3Y

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Warning

· **Hazard-determining components of labelling:**

toluene

· **Hazard statements**

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

GB
(Contd. on page 11)

Trade name: BODY P307 4:1 FILLING PRIMER

(Contd. of page 10)

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.

Department issuing SDS: Department of Quality Control

Contact:

HB BODY S.A
Ms Olympia Stamkou
Ph: +30 2310 790 032
fax: +30 2310 790 033
email: stamkou@hbbody.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity - dermal – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

*** Data compared to the previous version altered.**

GB

(Contd. on page 12)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 11)

* **Annex: Exposure scenario 1**

· **Short title of the exposure scenario**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9b Fillers, putties, plasters, modelling clay

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Article category** AC1 Vehicles

· **Environmental release category** ERC2 Formulation into mixture

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** The substance is main component.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** Use only on hard ground.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Pregnant women should strictly avoid inhalation or skin contact.

Avoid contact with the skin.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· **Soil**

Prevent contamination of soil.

(Contd. on page 13)

Trade name: BODY P307 4:1 FILLING PRIMER

(Contd. of page 12)

The product is only processed over the concrete collecting basin.

- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** This product is to be used by professional technicians only.
- **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB

(Contd. on page 14)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 13)

* **Annex: Exposure scenario 2**

· **Short title of the exposure scenario**

· **Sector of Use** SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** Raw material.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting worker exposure**

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** Keep out of the reach of children.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

No special measures required.

Provide explosion-proof electrical equipment.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water** Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

(Contd. on page 15)

GB

Trade name: BODY P307 4:1 FILLING PRIMER

(Contd. of page 14)

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB

(Contd. on page 16)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 15)

* **Annex: Exposure scenario 3**

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** Raw material.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water** Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

(Contd. on page 17)

Trade name: BODY P307 4:1 FILLING PRIMER

(Contd. of page 16)

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB

(Contd. on page 18)

Trade name: **BODY P307 4:1 FILLING PRIMER**

(Contd. of page 17)

* **Annex: Exposure scenario 4**

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** Raw material.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

· **Other operational conditions affecting worker exposure**

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· **Soil**

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer** This product is to be used by professional technicians only.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.