



	COLOUR	APPLICATION								APPEARANCE		MIXING		DRYING			PAGE	
		STEEL	E-COATING	GALVANIZED	ALUMINIUM	ALUMINIUM RIMS	FIBERGLASS	HARD PLASTIC	SOFT PLASTIC	SPECIFIC WEIGHT kg/l	PACKAGING kg/liter	MIXING RATIO % by weight	POTLIFE at 20°C.	SANDING TIME AT 20°C.	SANDING TIME 60°C.	TEMP. RESISTANCE °C		
GAP 00	GAPOL		●			●	●	●	●		1,83	2kg/1,09l	2%	4-5'	<25'	10'	80 °C	61
GAP 10	MULTI		●		●	●		●		1,81	2kg/1,10l	2%	4-5'	<20'	5'	80 °C	61	
GAP 20	FINE		●					●		1,68	2kg/1,19l	2%	4-5'	<15'	10'	80 °C	61	
GAP 30	LIGHT		●		●	●		●		1,36	1,5kg/1,09l	2%	4-5'	<15-20'	5-10'	80 °C	62	
GAP 31	ULTRA LIGHT		●	●	●	●		●		1	1kg/1l	1-3%	3-5'	<30'	4'-5'	80 °C	62	
GAP 33	EXTRA LIGHT		●	●	●	●		●		1	3kg/3l	1-3%	3-5'	<30'	4'-5'	80 °C	62	
GAP 40	FIBER		●			●		●		1,61	1,8kg/1,11l	2%	4-5'	<20'	10'	80 °C	63	
GAP 50	ALU		●		●	●	●	●		1,53	2kg/1,30l	2%	4-6'	<20'	10'	80 °C	63	
GAP 70	PLASTFILL							●	●	1,3	1kg/0,75l	1-3%	3-5'	<30'	4'-5'	80 °C	64	
GAP 80	UV		●		●	●		●	●	1,75	500 gr cartridge	-	∞	-	2'-5' @7mW/cm²	80 °C	65	
DEB 12	PB - SN		●		●	●			TSP 030	TSP 030	1,3	1L/1,3kg	1-3%	3-4'	<30'	-	180° C MAX 15'!	63

Hardener

- GAP 51** For all GAP putties
- DEB 51** For DEB 12
- GAP 80** No hardener needed

Storage

Shelf life putty: 18 months
Shelf life BPO hardener: 12 months



Dry



Frost free



Not in direct
sunlight



Closed tin