

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 1 of 13

POR-15 FUEL TANK SEALER

SECTION 1: Identification

Product identifier

Product name: POR-15 FUEL TANK SEALER

Product code: 49201; 49204; 49205; 49208; 49216; 49255; 249204;
249205; 249208; 249216; 249255



Recommended use of the product and restriction on use

Relevant identified uses: Paints and coatings.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

P.O.R. Products
38 Portman Road
New Rochelle, NY 10801
914-636-0700

Supplier:

Australia

Sydney Automotive Paints & Equipment Pty Ltd
A3 / 366 Edgar Street
Condell Park, NSW 2200 Australia
+61 2 9772 9000

Emergency telephone number:

Australia

Emergency telephone AU Poison Information Centre 13 11 26

General medical information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

Transport information: +61 2 9772 9000 (Mon to Fri, 08:00-16:00 AEST)

SECTION 2: Hazard(s) identification

GHS classification:

Flammable liquids, category 3

Eye irritation, category 2A

Skin irritation, category 2

Respiratory sensitization, category 1

Aspiration hazard, category 1

Acute toxicity (inhalation), category 4

Specific target organ toxicity - single exposure, category 3, respiratory irritation

Specific target organ toxicity - single exposure, category 3, central nervous system

Specific target organ toxicity - repeated exposure, category 1

Carcinogenicity, category 2

Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H226 Flammable liquid and vapor

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 2 of 13

POR-15 FUEL TANK SEALER

H319 Causes serious eye irritation
H315 Causes skin irritation
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
H304 May be fatal if swallowed and enters airways
H332 Harmful if inhaled
H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness
H372 Causes damage to organs through prolonged or repeated exposure
H351 Suspected of causing cancer

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 Keep container tightly closed
P240 Ground/bond container and receiving equipment
P241 Use explosion-proof electrical/ventilating/light/equipment
P242 Use only non-sparking tools
P243 Take precautionary measures against static discharge
P280 Wear protective gloves/protective clothing/eye protection/face protection
P264 Wash skin thoroughly after handling
P285 In case of inadequate ventilation wear respiratory protection
P271 Use only outdoors or in a well-ventilated area
P260 Do not breathe dust/fume/gas/mist/vapors/spray
P270 Do not eat, drink or smoke when using this product
P201 Obtain special instructions before use
P202 Do not handle until all safety precautions have been read and understood
P303+P361+P353 If on skin (or hair): Immediately remove/take off all contaminated clothing. Rinse skin with water/shower
P370+P378 In case of fire: Use agents recommended in section 5 for extinction
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P321 Specific treatment (see supplemental first aid instructions on this label).
P362 Take off contaminated clothing and wash before reuse
P302+P352 If on skin: Wash with soap and water
P332+P313 If skin irritation occurs: Get medical advice/attention
P331 Do not induce vomiting
P301+P310 If swallowed: Immediately call a poison center or doctor/physician
P304+P340+P312 If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell
P308+P313 If exposed or concerned: Get medical advice/attention
P405 Store locked up
P403+P233 Store in a well ventilated place. Keep container tightly closed
P501 Dispose of contents and container as instructed in Section 13

Hazards not otherwise classified: None

SECTION 3: Composition and information on ingredients

| Identification | Name | Weight % |
|---------------------------|---|----------|
| CAS number: 67815-87-6 | Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol | 35-65 |

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 3 of 13

POR-15 FUEL TANK SEALER

| | | |
|---------------------------|--|-------|
| CAS number: 64742-95-6 | Solvent naphtha (petroleum), light arom. | 30-35 |
| CAS number: 101-68-8 | 4,4'-Methylenediphenyl diisocyanate | 5-13 |
| CAS number: 95-63-6 | 1, 2, 4-Trimethylbenzene | <12 |
| CAS number: 9016-87-9 | Isocyanic acid, polymethylenepolyphenylene ester | 3-8 |
| CAS number: 26447-40-5 | Methylenediphenyl diisocyanate | <5 |
| CAS number: 7429-90-5 | Aluminum | <3 |
| CAS number: 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | <2 |
| CAS number: 1330-20-7 | Xylene | <1 |
| CAS number: 98-82-8 | Cumene | <0.5 |

Additional Information: None

SECTION 4: First aid measures

Description of first aid measures

General notes:

Get medical attention if you feel unwell

After inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

Take precautions to ensure your own safety

Remove source of exposure or move person to fresh air

Get medical advice if you feel unwell or concerned

After skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 4 of 13

POR-15 FUEL TANK SEALER

Get medical advice if eye irritation persists

After swallowing:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

May cause breathing difficulty, asthma attack, nausea, allergic reaction

Delayed symptoms and effects:

Not determined or not applicable.

Immediate medical attention and special treatment

Specific treatment:

Not determined or not applicable.

Notes for the doctor:

Contains isocyanates, consult literature for specific treatment

SECTION 5: Fire fighting measures

Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam

Unsuitable extinguishing media:

Do not use a water stream as an extinguisher

Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors

Vapors can flow to distant ignition sources and flashback

Liquid is volatile and may generate an explosive atmosphere

Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit

Special precautions:

Shut off sources of ignition

Carbon monoxide and carbon dioxide may form upon combustion

Heating causes a rise in pressure, risk of bursting and combustion

Hazchem: •3Y

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation

Ensure air handling systems are operational

Wear protective eye wear, gloves and clothing

Beware of vapors accumulating to form explosive concentrations

Vapors can accumulate in low areas

Environmental precautions:

Should not be released into the environment

Prevent from reaching drains, sewer or waterway

Methods and material for containment and cleaning up:

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 5 of 13

POR-15 FUEL TANK SEALER

Wear protective eye wear, gloves and clothing
Use spark-proof tools and explosion-proof equipment
Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders)
Dispose of contents / container in accordance with local regulations

Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage precautions

Precautions for safe handling:

Use only with adequate ventilation.
Avoid breathing mist or vapor.
Do not eat, drink, smoke or use personal products when handling chemical substances.
Take precautionary measures against electrostatic discharges.
Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.
Protect from freezing and physical damage.
Store in a cool, well-ventilated area.
Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

SECTION 8: Exposure controls and personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

| Country (Legal Basis) | Substance | Identifier | Permissible concentration |
|-----------------------|-------------------------------------|------------|--|
| Australia | Aluminum | 7429-90-5 | TWA: 10 mg/m ³ (metal dust); TWA: 5 mg/m ³ (welding fumes as Al); TWA: 5 mg/m ³ (Pyro Powders, as Al) |
| | 4,4'-Methylenediphenyl diisocyanate | 101-68-8 | TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ |
| | Cumene | 98-82-8 | TWA: 125 mg/m ³ (25 ppm) ; STEL: 375 mg/m ³ (75 ppm) |
| | Xylene | 1330-20-7 | TWA: 350 mg/m ³ (80 ppm) ; STEL: 655 mg/m ³ (150 ppm) |

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls.
Biological monitoring may also be appropriate for some substances.

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.
Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 6 of 13

POR-15 FUEL TANK SEALER

Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

| | |
|--|--|
| Appearance | Semi-Transparent Silver Colored Liquid |
| Odor | Not determined or not available. |
| Odor threshold | Not determined or not available. |
| pH | Not determined or not available. |
| Melting point/freezing point | Not determined or not available. |
| Initial boiling point/range | >284°F (>140°C) |
| Flash point (closed cup) | >103°F (>39.4°C) |
| Evaporation rate | Not determined or not available. |
| Flammability (solid, gas) | Not determined or not available. |
| Upper flammability/explosive limit | Not determined or not available. |
| Lower flammability/explosive limit | Not determined or not available. |
| Vapor pressure | 38 mmHg |
| Vapor density | Not determined or not available. |
| Density | 1.09 g/mL |
| Relative density | Not determined or not available. |
| Solubilities | Not miscible. |
| Partition coefficient (n-octanol/water) | Not determined or not available. |
| Auto/Self-ignition temperature | Not determined or not available. |
| Decomposition temperature | Not determined or not available. |
| Dynamic viscosity | 200-500 cPs |
| Kinematic viscosity | Not determined or not available. |
| Explosive properties | Not determined or not available. |
| Oxidizing properties | Not determined or not available. |

Other information

| | |
|--------------------|-----------------------------|
| VOC Content | 310 g/L (US EPA Method 24A) |
|--------------------|-----------------------------|

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 7 of 13

POR-15 FUEL TANK SEALER

| | |
|---------------------------------|-------------------|
| Recommended Storage Temperature | 50°F - 95°F |
| Recommended Shelf Life | 3 Years Un-Opened |

SECTION 10: Stability and reactivity

Reactivity:

Does not react under normal conditions of use and storage.

Chemical stability:

Stable under normal conditions of use and storage.

Possibility of hazardous reactions:

None under normal conditions of use and storage.

Conditions to avoid:

Keep away from heat, sparks and flames.

Incompatible materials:

None known.

Hazardous decomposition products:

None known.

SECTION 11: Hazard information

Acute toxicity

Assessment: Harmful if inhaled

Product data: No data available.

Substance data:

| Name | Route | Result |
|--|------------|--|
| Isocyanic acid, polymethylenepolyphenylene ester | inhalation | LC50 - Rat - 490 mg/m ³ /4h |
| Methylenediphenyl diisocyanate | inhalation | LC50 - Rat - 369 mg/cu m/4 h |
| 4,4'-Methylenediphenyl diisocyanate | inhalation | LC50 - Rat - 369 mg/cu m/4 h |
| Xylene | dermal | LD50 - Rat - > 1,700 mg/kg |
| | inhalation | LC50 - Rat - 5,000 ppm/4 h |
| 1, 2, 4-Trimethylbenzene | inhalation | LC50 - Rat - 18,000 mg/m ³ |

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 8 of 13

POR-15 FUEL TANK SEALER

| Name | Result |
|---|---------------------------|
| Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol | Irritating to the skin. |
| Isocyanic acid, polymethylenepolyphenylene ester | Moderate skin irritation. |
| Methylenediphenyl diisocyanate | Irritating to the skin. |
| 4,4'-Methylenediphenyl diisocyanate | Irritating to the skin. |
| Naphtha (petroleum), hydrotreated heavy | Irritating to the skin. |
| Xylene | Irritating to the skin. |
| 1, 2, 4-Trimethylbenzene | Irritating to the skin. |

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

| Name | Result |
|---|--------------------------------|
| Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol | Irritating effect on the eyes. |
| Isocyanic acid, polymethylenepolyphenylene ester | Irritating effect on the eyes. |
| Methylenediphenyl diisocyanate | Moderate eye irritation. |
| 4,4'-Methylenediphenyl diisocyanate | Moderate eye irritation. |
| 1, 2, 4-Trimethylbenzene | Irritating effect on the eyes. |

Respiratory or skin sensitization

Assessment: May cause allergy or asthma symptoms or breathing difficulties if inhaled

Product data:

No data available.

Substance data:

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 9 of 13

POR-15 FUEL TANK SEALER

| Name | Result |
|---|--|
| Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol | Sensitization possible through skin and respiratory contact. |
| Isocyanic acid, polymethylenepolyphenylene ester | May cause sensitization by respiratory contact. |
| Methylenediphenyl diisocyanate | May cause sensitization by inhalation and skin contact. |
| 4,4'-Methylenediphenyl diisocyanate | May cause sensitization by inhalation and skin contact. |
| Cumene | No skin irritation |
| | No eye irritation |

Carcinogenicity

Assessment: Suspected of causing cancer

Product data: No data available.

Substance data:

| Name | Species | Result |
|--|--|-----------------------------|
| Methylenediphenyl diisocyanate | Methylenediphenyl diisocyanate | May cause cancer. |
| 4,4'-Methylenediphenyl diisocyanate | | May cause cancer. |
| Solvent naphtha (petroleum), light arom. | Solvent naphtha (petroleum), light arom. | Component may cause cancer. |

International Agency for Research on Cancer (IARC):

| Name | Classification |
|--|--|
| Isocyanic acid, polymethylenepolyphenylene ester | Group 3 - Not classifiable as to its carcinogenicity to humans |
| Xylene | Group 3 - Not classifiable as to its carcinogenicity to humans |
| Cumene | Group 2B - Possibly carcinogenic to humans |

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

| Name | Result |
|--|----------------------------|
| Solvent naphtha (petroleum), light arom. | May cause genetic defects. |

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 10 of 13

POR-15 FUEL TANK SEALER

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: May cause respiratory irritation May cause drowsiness or dizziness

Product data:

No data available.

Substance data:

| Name | Result |
|---|--|
| Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol | May cause respiratory tract irritation through single or repeated exposure. |
| Isocyanic acid, polymethylenepolyphenylene ester | Component affects the respiratory system through single and repeated exposure. |
| Methylenediphenyl diisocyanate | Component affects the respiratory system through single and repeated exposure. |
| 4,4'-Methylenediphenyl diisocyanate | Component affects the respiratory system through single and repeated exposure. |
| Naphtha (petroleum), hydrotreated heavy | Component affects the central nervous system. |
| Cumene | Component affects the respiratory system. |
| 1, 2, 4-Trimethylbenzene | Component affects the respiratory system. |

Specific target organ toxicity (repeated exposure)

Assessment: Causes damage to organs through prolonged or repeated exposure

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: May be fatal if swallowed and enters airways

Product data:

No data available.

Substance data:

| Name | Result |
|--|--|
| Naphtha (petroleum), hydrotreated heavy | May be fatal if swallowed and enters airway. |
| Solvent naphtha (petroleum), light arom. | May be fatal if swallowed and enters airway. |

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 11 of 13

POR-15 FUEL TANK SEALER

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

| Name | Result |
|--------------------------|---|
| Cumene | EC50 - Daphnia magna - 1.4 mg/L - 24 h |
| | LC50 - Pimephales promelas - 6.32 mg/L - 96 h |
| 1, 2, 4-Trimethylbenzene | LC50 - Pimephales promelas - 7.72 mg/L - 96 h |

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

Persistence and degradability

Product data: No data available.

Substance data: No data available.

Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.


SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

Australian Dangerous Goods (ADG)

| | |
|-------------------------------|---|
| UN number | 1263 |
| UN proper shipping name | Paint |
| UN transport hazard class(es) | 3  |
| Packing group | III |
| Environmental hazards | None |
| Special precautions for user | None |
| Hazchem/Emergency Action Code | •3Y |

Safety Data Sheet


According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017


Page 12 of 13

POR-15 FUEL TANK SEALER

International Maritime Dangerous Goods (IMDG)

| | |
|-------------------------------|---|
| UN number | 1263 |
| UN proper shipping name | Paint |
| UN transport hazard class(es) | 3  |
| Packing group | III |
| Environmental hazards | None |
| Special precautions for user | None |
| EmS number | F-E, S-E |
| Stowage category | A |
| Excepted quantities | E1 |
| Limited quantity | 5L |

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

| | |
|-------------------------------|--|
| UN number | 1263 |
| UN proper shipping name | Paint |
| UN transport hazard class(es) | 3  |
| Packing group | III |
| Environmental hazards | None |
| Special precautions for user | None |
| ERG code | 3L |
| Excepted quantities | E1 |
| Passenger and cargo | 60L |
| Cargo aircraft only | 220L |
| Limited quantity | 10L |

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

| | |
|--------------------|------|
| Bulk Name | None |
| Ship type | None |
| Pollution category | None |

SECTION 15: Regulatory information

Australia regulations

Australian Inventory of Chemical Substances (AICS):

| | | |
|------------|---|--------|
| 67815-87-6 | Isocyanic acid, polymethylenepolyphenylene ester, polymer with 1,2-ethanediamine, 2-methyloxirane and 1,2-propanediol | Listed |
| 9016-87-9 | Isocyanic acid, polymethylenepolyphenylene ester | Listed |
| 26447-40-5 | Methylenediphenyl diisocyanate | Listed |
| 101-68-8 | 4,4'-Methylenediphenyl diisocyanate | Listed |

Safety Data Sheet

According to the Australian Work Health and Safety Regulations

Initial preparation date: 10.10.2017

Page 13 of 13

POR-15 FUEL TANK SEALER

| | | |
|------------|--|--------|
| 64742-48-9 | Naphtha (petroleum), hydrotreated heavy | Listed |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | Listed |
| 7429-90-5 | Aluminum | Listed |
| 1330-20-7 | Xylene | Listed |
| 98-82-8 | Cumene | Listed |
| 95-63-6 | 1, 2, 4-Trimethylbenzene | Listed |

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP):

| | | |
|-----------|--------|--------|
| 1330-20-7 | Xylene | Listed |
|-----------|--------|--------|

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This SDS was authored in accordance with the Australian Work Health and Safety Regulations and supplemented by the Australian Code of Practice on the Preparation of Safety Data Sheets for Hazardous Chemicals. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 3-2-0

HMIS: 3-2-0

Initial preparation date: 10.10.2017

Additional information:

Version: 1.0

End of Safety Data Sheet