

# G3 Liquid

Advanced Abrasive Compound



## Product Description

Advanced G3 Liquid is a one-step system that provides a fast cutting action and a high gloss finish. It combines all the reliability and other advantages of G3 Paste with a reduced clean up time when compounding by machine. It provides the user with improved versatility, quality and speed to final finish versus competitive products. AG3 has been tested against all major paint brands and has proven compliant to remove defects from all modern paint systems. Using the product with water will result in maximum performance benefits.

## Product Information

Size	Code	Ctn Qty
500ml (17 fl.oz.)	AG3-700	12
1 litre (34 fl.oz.)	AG3-1400	6
1 US Gallon (3.785 ltrs)	AG3-5300	2

## Technical Information

Appearance: **White coloured liquid**  
Viscosity: **High viscosity**  
VOC Content: **10.9% of total product**  
Relative Density: **1.47**  
pH: **8.6**  
Paint Type Compliance: **MS & HS**

## Key Benefits

• Versatile	Can be used on fresh and cured paintwork
• Permanent Finish	Removes P1500 abrasive paper marks without the use of fillers
• Rapid Cutting Action	Improved cutting action quickens the process
• Reduced Clean Up Time	Less water is required during use which reduces throw-off

## Use With


### Primary Application



G Mop 6" Advanced  
Compounding Foam  
**AGM-CF**



G Mop 6" Advanced  
Back Plate  
**AGM-BP14** (14mm)  
**AGM-BP58** (5/8")




Farécla Finishing  
Cloth  
**FC-3**

### Secondary Application




G Mop 6" Advanced  
Compounding Head  
**AGM-14** (14mm)  
**AGM-58** (5/8")




Farécla Finishing  
Cloth  
**FC-3**


## How To Use




Soak pad in clean  
water  
**AGM-CF** (pad)  
**AGM-BP** (back  
plate)




Squeeze out excess  
water and attach to  
polishing machine  
**ATTACH**



Spin off excess  
water until there is  
no over spray  
from pad




Shake well, apply  
a small amount of  
product and  
spread with pad to  
reduce throw off  
**SHAKE**  
**POUR**




Compound until  
marks have been  
removed - speed  
1500 - 1800rpm  
**1500 - 1800rpm**



Keep pad damp  
**WSB** (water bottle)



If necessary add  
more compound  
to completely  
remove the marks  
**POUR**



Wipe clean with  
Finishing Cloth  
**FC-3** (cloth)

\*It is always recommended to test on an inconspicuous area prior to general use