

TECHNICAL SHEET

POL 10 – Finixa one step polish paste 1l

Purpose

For the fast removal of blemishes on newly repaired and aged top-coats. Also suitable for the removal of deep scratches and for the conditioning of heavily weathered paints.

Product description

Composition: Aluminium oxide, hydrocarbon, water, silicon free.

Physiological details: Due to its chemical formula this polish is harmless when used in accordance with its intended application.

Application

Preferably mechanical rotating or eccentric with recommended polishing discs.

All lacquered surfaces in the automotive, nautical or timbered areas (paints, single or multi-component systems, water-based paints, powder coatings, scratch-resistant clear lacquers containing solvents). Not for use on matt lacquers.

Caution

In order to obtain an optimum, microscratch-free surface, the fast-acting POL 10 should not be mixed under any circumstances with other polishes or solvents otherwise this will invalidate all guarantees.

Packaging

Packaging: 1 kg/ltr PE plastic bottle according to specification.

Storage

Can be stored at temperatures between 15 and 25 °C in the original container for 24 months. The container must be protected from frost and direct sunlight when storing and transporting!

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out. The client has to decide on the products suitability for their own applications.