

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Finixa spray anti-gravel black 400ml  
Product code : TSP 230  
Vaporizer : Aerosol

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use, Consumer use  
Function or use category : Industrial spraying, Non industrial spraying

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Chemicar Europe NV  
Baarbeek 2  
2070 Zwijndrecht  
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89  
[info@chemicar.eu](mailto:info@chemicar.eu)

#### 1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229  
Serious eye damage/eye irritation, Category 2 H319  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Specific target organ toxicity — Repeated exposure, Category 2 H373  
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412  
Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) : Danger

Hazardous ingredients : Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics; butanone; ethyl methyl ketone; 1-methoxy-2-propanol; monopropylene glycol methyl ether; stoddard solvent; Low boiling point naphtha—; unspecified; [A colourless, refined petroleum distillate that is free from rancid or objectionable odours and that boils in a range of approximately 148,8°C to 204,4 °C (300°F to 400°F).]

Hazard statements (CLP) : H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs (central nervous system) through prolonged or repeated exposure.  
H412 - Harmful to aquatic life with long lasting effects.

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe dusts or mists. P271 - Use only outdoors or in a well-ventilated area. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403 - Store in a well-ventilated place. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.

### Scandinavian countries regulation

Denmark

MAL code : 5-6

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5	10 - 25	Flam. Gas 1, H220 Press. Gas
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	(CAS-No.) 68920-06-9 (EC-No.) 920-750-0	10 - 25	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
butanone; ethyl methyl ketone	(CAS-No.) 78-93-3 (EC-No.) 201-159-0 (EC Index-No.) 606-002-00-3	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0	2.5 - 10	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
1-methoxy-2-propanol; monopropylene glycol methyl ether	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3	2.5 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
butane (containing ≥ 0,1% butadiene (203-450-8))	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-01-8	2.5 - 10	Flam. Gas 1, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	(EC-No.) 926-605-8	1 - 2.5	Flam. Liq. 2, H225 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
isobutane (containing ≥ 0,1% butadiene (203-450-8))	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (EC Index-No.) 601-004-01-8	1 - 2.5	Flam. Gas 1, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CARBON BLACK	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	0.1 - 1	Self-heat. 1, H251
HYDROGENATED TALLOWALKONIUM CHLORIDE	(CAS-No.) 61789-72-8 (EC-No.) 263-081-3	0.25 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400
ethanol; ethyl alcohol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	0.1 - 1	Flam. Liq. 2, H225

Full text of H-statements: see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: No irritant effect.
First-aid measures after eye contact	: In case of contact, immediately rinse eyes with plenty of water for at least 15 minutes. Consult an ophthalmologist if irritation persists. Rinse opened eye for several minutes under running water. Then consult doctor.
First-aid measures after ingestion	: Do not induce vomiting. Immediately call a POISON CENTER/doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

#### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Alcohol resistant foam. extinguishing powder. Water fog. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

No additional information available

#### 5.3. Advice for firefighters

Protection during firefighting	: Approved respirator.
--------------------------------	------------------------

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable protective clothing. Keep public away.
------------------	--

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Only qualified personnel equipped with suitable protective equipment may intervene.
----------------------	---

##### 6.1.2. For emergency responders

No additional information available

#### 6.2. Environmental precautions

Do not discharge into drains or rivers. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment	: Provide adequate ventilation.
Methods for cleaning up	: Do not flush with water.

#### 6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Ensure adequate air ventilation.
Precautions for safe handling	: Handle and open container with care. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. Do not spray on an open flame or other ignition source.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool place.
Storage conditions	: Keep cool. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep dry.
Special rules on packaging	: Store in a closed container.

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace		
<b>propane (74-98-6)</b>		
WEL	Long-term value	1800 mg/m <sup>3</sup>
<b>Butanone (78-93-3)</b>		
WEL	Short-term value Long-term value Sk, BMGV	899 mg/m <sup>3</sup> , 300 ppm 600 mg/m <sup>3</sup> , 200 ppm
<b>1-methoxy-2-propanol (107-98-2)</b>		
WEL	Short-term value: Long-term value Sk	560 mg/m <sup>3</sup> , 150 ppm 375 mg/m <sup>3</sup> , 100 ppm
<b>106-97-8 butane (containing &lt; 0.1% butadiene (203-450-8))</b>		
WEL	Short-term value: Long-term value Carc	1810 mg/m <sup>3</sup> , 750 ppm 1450 mg/m <sup>3</sup> , 600 ppm (if more than 0.1% of buta-1.3-diene)
<b>75-28-5 isobutane (containing &lt; 0,1 % butadiene (203-450-8))</b>		
WEL	Short-term value Long-term value	2400 mg/m <sup>3</sup> 1900 mg/m <sup>3</sup>
<b>1333-86-4 Carbon black</b>		
WEL	Short-term value Long-term value	7 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup>
<b>Ethanol (64-17-5)</b>		
WEL	Long-term value	1920 mg/m <sup>3</sup> , 1000 ppm
<b>DNELs</b>		
<b>Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics (68920-06-9)</b>		
Oral	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	699 mg/kg bw/day (Consumer)
		773 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	608 mg/m <sup>3</sup> (Consumer)
		2,035 mg/m <sup>3</sup> (Worker)
<b>Butanone (78-93-3)</b>		
Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer)
		1,161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m <sup>3</sup> (Consumer)
		600 mg/m <sup>3</sup> (Worker)
<b>Reaction mass of ethylbenzene and xylene</b>		
Oral	DNEL Long term-systemic	1.6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer)
		180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	289 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	14.8 mg/m <sup>3</sup> (Consumer)
		77 mg/m <sup>3</sup> (Worker)

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

1-methoxy-2-propanol (107-98-2)		
Oral	DNEL Long term-systemic	3.3 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	18.1 mg/kg bw/day (Consumer)
		50.6 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	553.5 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	43.9 mg/m <sup>3</sup> (Consumer)
		369 mg/m <sup>3</sup> (Worker)
1-methoxy-2-propanol (107-98-2)		
Oral	DNEL Long term-systemic	3.3 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	18.1 mg/kg bw/day (Consumer)
		50.6 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local	553.5 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	43.9 mg/m <sup>3</sup> (Consumer)
		369 mg/m <sup>3</sup> (Worker)
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes		
Oral	DNEL Long term-systemic	1,301 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	1,377 mg/kg bw/day (Consumer)
Inhalative	DNEL Long term-systemic	1,131 mg/m <sup>3</sup> (Consumer)
		5,306 mg/m <sup>3</sup> (Worker)
PNECs		
Reacton mass of ethylbenzene and xylene		
PNEC Freshwater	0.327 mg/l (Undefined)	
PNEC Marine water	0.327 mg/l (Undefined)	
PNEC Freshwater sediment	12.46 mg/l(dry weight) (Undefined)	
PNEC Soil	2.31 (Undefined)	
PNEC Sewage Treatment Plant	6.58 mg/l (Undefined)	
PNEC Marine water sediment	12.46 mg/l(dry weight) (Undefined)	
107-98-2 1-methoxy-2-propanol		
PNEC Freshwater	10 mg/l (Undefined)	
PNEC Freshwater sediment	41.6 mg/l(dry weight) (Undefined)	
PNEC Soil	2.47 (Undefined)	
Ingredients with biological limit values		
78-93-3 butanone		
BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one	
Additional Occupational Exposure Limit Values for possible hazards during processing		
110-54-3 n-hexane		
WEL	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm	

## 8.2. Exposure controls

### Appropriate engineering controls:

Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol.

### Personal protective equipment:

Gloves. Protective goggles.

### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Nitrile rubber gloves	Nitrile rubber (NBR)	5 (> 240 minutes)	>= 0.5		EN ISO 374

### Eye protection:

Wear closed safety glasses. EN 166

Type	Use	Characteristics	Standard
			EN 166

### Skin and body protection:

Wear suitable protective clothing

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Standard		
	EN 13034		
<b>Respiratory protection:</b>			
Wear appropriate mask			
Device	Filter type	Condition	Standard
Gas filters	Filter AX (brown), Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Short term exposure	
Self-contained breathing apparatus (SCBA)	Filter AX (brown), Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust	Long term exposure	

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -44.5 °C
Flash point	: -97 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 5100 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: ≈ 0.79 g/cm <sup>3</sup> 20°C
Solubility	: Practically not miscible. Organic solvent:67,0%
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: In use, may form flammable/explosive vapour-air mixture.
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.7 vol %
Upper explosive limit (UEL)	: 20 vol %

### 9.2. Other information

VOC content	: ≈ 529.6 g/l VOC-CH: 66,78%
-------------	------------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: Not classified

LD/LC50 values relevant for classification		
Hydrocarbons, C7-C9, n-alkanes, isoalkanes,cyclics (68920-06-9)		
Oral	LD 50	>5,000 mg/kg (rat)
Dermal	LD 50	>2,800 mg/kg (rabbit)
Inhalative	LC50/4h	>23 mg/l (rat)
Butanone (78-93-3)		
Oral	LD50	>2,193 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit) 5,000 mg/kg (rbt)
Reaction mass of ethylbenzene and xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
1-methoxy-2-propanol (107-98-2)		
Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/6h	27,596 mg/m <sup>3</sup> (rat)
Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes		
Oral	LD50	16,750 mg/kg (rat)
Dermal	LD50	3,350 mg/kg (rat)
Inhalative	LC50/4h	259,354 mg/l (rat)

Finixa spray anti-gravel black 400ml	
Vaporizer	Aerosol

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: Toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

Aquatic toxicity	
Hydrocarbons, C7-C9, n-alkanes, isoalkanes,cyclics (68920-06-9)	
NOELR (72h)	10 mg/l (Pseudokirchneriella subcapitata)
EL50 (72h)	10-30 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	>13.4 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0.17 mg/l (Daphnia magna)
LOEC (21 days)	0.32 mg/l (Daphnia magna)
EC50/48h	3 mg/l (Daphnia magna)



# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

<b>Butanone (78-93-3)</b>	
LC50/96h	2,993 mg/l (Pimephales promelas)
EC50/48h	308 mg/l (Daphnia magna)
<b>Reaction mass of ethylbenzene and xylene</b>	
NOEC	1.3 mg/l (Fish)
NOEC (7 day)	0.96 mg/l (Daphnia magna)
NOEC (72h)	0.44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC50/96h	8.9-16.4 mg/l (Pimephales promelas)
EC50/48h	3.2-9.5 mg/l (Daphnia magna)
<b>1-methoxy-2-propanol (107-98-2)</b>	
LC50/96h	6,812 mg/l (Fish)
EC50/48h	23,300 mg/l (Daphnia magna)
<b>Hydrocarbons, C6-C7, isoalkanes, cycloalkanes max. 5% n-hexanes</b>	
NOELR (21d)	3.818 mg/l (Daphnia magna)
NOELR (28d)	2.187 mg/l (Oncorhynchus mykiss)
EL50(48h)	17.06 mg/l (Daphnia magna)
LL50 (96h)	9.776 mg/l (Oncorhynchus mykiss)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains.
Product/Packaging disposal recommendations	: Disposal must be done according to official regulations.
HP Code	: HP3 - "Flammable:" — flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; — flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; — flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; — flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; — water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
<b>14.1. UN number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>Transport document description</b>			
UN 1950 , 2.1, (D)	UN 1950 , 2.1	UN 1950 , 2.1	UN 1950 , 2.1
<b>14.3. Transport hazard class(es)</b>			
2.1	2.1	2.1	2.1



# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

			
---	---	--	---

### 14.4. Packing group

Not applicable	Not applicable	Not applicable	Not applicable
----------------	----------------	----------------	----------------

### 14.5. Environmental hazards

Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No
---------------------------------------	--	---------------------------------------	---------------------------------------

No supplementary information available

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR)	: 5F
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E0
Tunnel restriction code (ADR)	: D

#### Transport by sea

Limited quantities (IMDG)	: 1 L
Excepted quantities (IMDG)	: E0
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

#### Air transport

No data available

#### Inland waterway transport

No data available

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : ≈ 529.6 g/l VOC-CH: 66,78%

#### 15.1.2. National regulations

##### Germany

Reference to AwSV : Water hazard class (WGK) 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Denmark

Class for fire hazard : Class I-1

Store unit : 1 liter

Classification remarks : F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product

Pregnant/breastfeeding women working with the product must not be in direct contact with the product

The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Self-heat. 1	Self-Heating Substances and Mixtures, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H251	Self-heating: may catch fire.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

# Finixa spray anti-gravel black 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*