

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : Weld-thru primer phosphate zinc 400ml  
UFI : JFD7-CHUS-MP9K-7NDN  
Product code : TSP 810

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Industrial use, Consumer use  
Use of the substance/mixture : Non industrial spraying  
Industrial spraying  
Function or use category : Coatings and paints, thinners, paint removers

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Chemical Europe NV  
Baarbeek 2  
2070 Zwijndrecht  
T +32 (0) 3 234 87 80 - F +32 (0) 3 234 87 89  
[info@chemicar.eu](mailto:info@chemicar.eu)

#### 1.4. Emergency telephone number

Emergency number : +32 (0) 3 760 08 09

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 1	H372
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2	H411

Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

GHS09

Signal word (CLP) :

Danger

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Contains	: acetone; propan-2-one; propanone; Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]; Reaction mass of ethylbenzene and xylene; Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)
Hazard statements (CLP)	: H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness. H372 - Causes damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe Dust/smoke/gas/mist/vapour/spray mist. P264 - Wash hands thoroughly after handling. P273 - Avoid release to the environment. P280 - Wear eye protection/facial protection. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 - Call a poison control centre/doctor if you feel unwell. P337+P313 - If eye irritation persists: Get medical advice/attention. P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P405 - Store locked up. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 - Dispose of the content and packaging to the local/regional/national/international regulations..
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking. EUH208 - Contains 2-Butanone oxime. May produce an allergic reaction.

### Scandinavian countries regulation

Denmark

MAL code : 5-6

## 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
acetone; propan-2-one; propanone	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8	25 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
butane (containing ≥ 0,1% butadiene (203-450-8))	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-01-8	10 – 25	Flam. Gas 1A, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5	2.5 – 10	Flam. Gas 1A, H220 Press. Gas
trizinc bis(orthophosphate)	(CAS-No.) 7779-90-0 (EC-No.) 231-944-3 (EC Index-No.) 030-011-00-6	2.5 – 10	Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS-No.) 64742-95-6 (EC-No.) 265-199-0 (EC Index-No.) 649-356-00-4	2.5 – 10	Carc. 1B, H350 Muta. 1B, H340 Asp. Tox. 1, H304
isobutane (containing ≥ 0,1% butadiene (203-450-8))	(CAS-No.) 75-28-5 (EC-No.) 200-857-2 (EC Index-No.) 601-004-01-8	2.5 – 10	Flam. Gas 1A, H220 Press. Gas Carc. 1A, H350 Muta. 1B, H340
Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)	(CAS-No.) 64742-82-1 (EC-No.) 919-446-0 (REACH-no) 01-2119458049-33	2.5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Reaction mass of ethylbenzene and xylene	(EC-No.) 905-588-0	1 – 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: No irritant effect.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Consult an ophthalmologist if irritation persists. Rinse opened eye for several minutes under running water. Then consult doctor.
First-aid measures after ingestion	: Do not induce vomiting. Immediately call a POISON CENTER/doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water fog. extinguishing powder. carbon dioxide (CO2). Alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 5.2. Special hazards arising from the substance or mixture

No additional information available

### 5.3. Advice for firefighters

Protection during firefighting : Approved respirator.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Keep public away.

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Ensure adequate air ventilation.

Methods for cleaning up : Do not flush with water.

### 6.4. Reference to other sections

SECTION 7. SECTION 8. SECTION 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Ensure adequate air ventilation.

Precautions for safe handling : Handle and open container with care. Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep cool. Protect from sunlight. Protect from heat and direct sunlight.

Special rules on packaging : Container should not be closed gas-tight. Store in a closed container.

### 7.3. Specific end use(s)

No additional information available

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Ingredients with limit values that require monitoring at the workplace:		
<b>67-64-1 Acetone</b>		
WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm	
<b>106-97-8 butane (met &lt; 0,1 % butadien (203-450-8))</b>		
WEL	Short-term value: 1810 mg/m <sup>3</sup> , 750 ppm Long-term value: 1450 mg/m <sup>3</sup> , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
<b>74-98-6 propane</b>		
WEL	Long-term value: 1800 mg/m <sup>3</sup>	
<b>75-28-5 isobutane (containing &lt; 0,1 % butadiene (203-450-8))</b>		
WEL	Short-term value: 2400 mg/m <sup>3</sup> Long-term value: 1900 mg/m <sup>3</sup>	
<b>DNEL's</b>		
<b>67-64-1 Acetone</b>		
Oral	DNEL Long term-systemic	62 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	62 mg/kg bw/day (Consumer) 186 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local DNEL Long term-systemic	2420 mg/m <sup>3</sup> (Worker) 200 mg/m <sup>3</sup> (Consumer) 1210 mg/m <sup>3</sup> (Worker)
<b>64742-82-1 Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)</b>		
Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	26 mg/kg bw/day (Consumer) 44 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	71 mg/m <sup>3</sup> (Consumer) 330 mg/m <sup>3</sup> (Worker)
<b>Reaction mass of ethylbenzeen en xyleen</b>		
Oral	DNEL Long term-systemic	1,6 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	108 mg/kg bw/day (Consumer) 180 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-local DNEL Long term-systemic	289 mg/m <sup>3</sup> (Worker) 14,8 mg/m <sup>3</sup> (Consumer) 77 mg/m <sup>3</sup> (Worker)
<b>PNEC's</b>		
<b>67-64-1 Acetone</b>		
PNEC Marine water	1,06 mg/l (Undefined)	
PNEC Freshwater sediment	30,4 mg/l(dry weight) (Undefined)	
PNEC Soil	29,5 (Undefined)	
PNEC Marine water sediment	3,04 mg/l(dry weight) (Undefined)	
<b>Reaction mass of ethylbenzeen en xylene</b>		
PNEC Freshwater	0,327 mg/l (Undefined)	
PNEC Marine water	0,327 mg/l (Undefined)	
PNEC Freshwater sediment	12,46 mg/l(dry weight) (Undefined)	
PNEC Soil	2,31 (Undefined)	
PNEC Sewage Treatment Plant	6,58 mg/l (Undefined)	
PNEC Marine water sediment	12,46 mg/l(dry weight) (Undefined)	

#### 8.2. Exposure controls

##### Appropriate engineering controls:

Wash hands before breaks and after work. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes. Remove contaminated clothes. Keep away from food, drink and animal feedingstuffs.

##### Personal protective equipment:

Gloves. Protective goggles.

##### Hand protection:

Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	5 (> 240 minutes), 6 (> 480 minutes)	> 0.5		EN ISO 374

### Eye protection:

Protective goggles

Type	Use	Characteristics	Standard
			EN 166

### Skin and body protection:

Wear suitable protective clothing

Type	Standard
	EN 13034

### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust

Device	Filter type	Condition	Standard
	Type AX - Low-boiling (<65 °C) organic compounds, Type P2, Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust		

### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol.
Colour	: No data available
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -44.5 °C
Flash point	: -97 °C
Auto-ignition temperature	: 365 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not self-igniting
Vapour pressure	: 2100 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0.766 g/cm <sup>3</sup>

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Solubility	: Moderately soluble in water. Practically not miscible. Organic solvent:79.5%
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Lower explosive limit (LEL)	: 0.6 vol %
Upper explosive limit (UEL)	: 13 vol %

### 9.2. Other information

VOC content	: 607 g/l VOC-CH 79,24%
-------------	-------------------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No additional information available

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

LD/LC50 values relevant for classification:		
<b>67-64-1 Acetone</b>		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	7800 mg/kg (rbt)
Inhalative	LC50/4h	>20 mg/l (rat)
<b>64742-82-1 Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)</b>		
Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3160 mg/kg (Rabbit)
<b>7779-90-0 trizinc bis(orthophosphate)</b>		
Oral	LD50	5000 mg/kg (rat)
<b>64742-95-6 Solvent naphtha (petroleum), light arom. Benzene&lt;0.1%</b>		
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (Rabbit)
Inhalative	LC50/4h	>10,2 mg/l (rat)
<b>Reaction mass of ethylbenzene and xylene</b>		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - water : Toxic to aquatic life.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

Aquatic toxicity:	
<b>67-64-1 Acetone:</b>	
EC50	8800 mg/l (Daphnia magna) 8300 mg/l (Fish)
<b>64742-82-1 Hydrocarbon, C9-C12, n-alkanes, iso-alkenes, cyclic, aromates(2-25%)</b>	
NOELR (72h)	1 mg/l (Pseudokirchneriella subcapitata)
EL50(48h)	10-22 mg/l (Daphnia magna)
EL50 (72h)	4,6-10 mg/l (Pseudokirchneriella subcapitata)
LL50 (96h)	10-30 mg/l (Oncorhynchus mykiss (96h))
NOEC (21 days)	0,097 mg/l (Daphnia magna)
LOEC (21 days)	0,203 mg/l (Daphnia magna)
<b>7779-90-0 trizinc bis(orthophosphate)</b>	
LC50/96h	0,14 mg/l (Oncorhynchus mykiss (96h))
EC50/48h	2,34 mg/l (Daphnia magna)
ErC(50) (72h)	0,14 mg/l (Ds)
<b>Reaction mass of ethylbenzene en xylene</b>	
NOEC	1,3 mg/l (Fish)
NOEC (7 day)	0,96 mg/l (Daphnia magna)
NOEC (72h)	0,44 mg/l (algae)
NOEC (28 d)	16 mg/l (Bacteria)
LC50/96h	8,9-16,4 mg/l (Pimephales promelas)
EC50/48h	3,2-9,5 mg/l (Daphnia magna)

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available



# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
<b>14.1. UN number</b>			
UN 1950	UN 1950	UN 1950	UN 1950
<b>14.2. UN proper shipping name</b>			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS
<b>Transport document description</b>			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS
<b>14.3. Transport hazard class(es)</b>			
2.1	2.1	2.1	2.1
<b>14.4. Packing group</b>			
Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available			

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : 5F  
Special provisions (ADR) : 190, 327, 344, 625  
Limited quantities (ADR) : 1I  
Excepted quantities (ADR) : E0  
Packing instructions (ADR) : P207  
Special packing provisions (ADR) : PP87, RR6, L2  
Mixed packing provisions (ADR) : MP9  
Transport category (ADR) : 2  
Special provisions for carriage - Packages (ADR) : V14  
Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
Special provisions for carriage - Operation (ADR) : S2

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Tunnel restriction code (ADR)	: D
<b>Transport by sea</b>	
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69

### Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

### Inland waterway transport

Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1 L
Excepted quantities (ADN)	: E0
Equipment required (ADN)	: PP, EX, A
Ventilation (ADN)	: VE01, VE04
Number of blue cones/lights (ADN)	: 1

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 607 g/l VOC-CH 79,24%

#### 15.1.2. National regulations

##### Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

##### Netherlands

Waterbevaarlijkheid : 1 - Black list substance

Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken

SZW-lijst van kankerverwekkende stoffen : Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SZW-lijst van mutagene stoffen	: Solvent naphtha (petroleum), light arom.; Low boiling point naphtha -unspecified; [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).] is listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed
<b>Denmark</b>	
Class for fire hazard	: Class I-1
Store unit	: 1 liter
Classification remarks	: F+ <Aerosol 1>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No additional information available

### SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

# Weld-thru primer phosphate zinc 400ml

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains . May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.